




P. +64 9 473 1602, 0800 ALUMAT  
 F. +64 9 473 8406  
 E. [info@alumat.co.nz](mailto:info@alumat.co.nz)  
 W. [www.alumat.co.nz](http://www.alumat.co.nz)

**PRODUCT**

**ALUMAT 15 D (Draining)**

**DESCRIPTION**

Extra Heavy Duty aluminium and infill entrance mat with water draining channels and elevated infills. Our top-of-the-line mat for all weather situations with 20 year frame warranty. Capable of discharging to mat well drainage point, either floor waste, or threshold drain.

**USES**

Mat depth 15mm – 20mm. Install in set downs 15mm TO 20mm deep

**FEATURES**

Elevated infills with water drain channels provide the best available water channelling and dirt containment option. Water is taken away from the mat surface, rather than holding and releasing when compressed by foot traffic. Ezi-clean with no under mat soiling. For use both inside and outside, where draining or evaporation channels are required. Variable depth FULL rubber base instead of strips, and extra thick aluminium provides uniform cushioning and weight distribution with no ‘clatter’ or distortion. Fully interlocking allows for complex mat shapes which can be seamlessly joined to make any width or depth mats. Choose from our range of colour infills.

**LIMITATIONS**

For use in set downs or matwells. For surface mounted mats with incorporated ramping option, see Alumat 10 I, 10 D, 10W, or 10 DW

Substrates must be properly prepared and level as per our specifications available on our website.

**PERFORMANCE**

Complies with all Australian and New Zealand building code requirements, including the following Fire safety. EN ISO 9239-1 Critical Flux  $\geq 8$  kw/m<sup>2</sup>. Slip test compliant in both wet and dry situations. AS/NZS3661.1

**MATERIALS**

Infills 100% air-entangled polypropylene with FR backing ( fire retardant) made by leading Dutch manufacturer, Vebe Floor Coverings for distribution in New Zealand exclusively by Alumat Flooring Solutions.

1720g/m<sup>2</sup>, pile thickness 4mm, O/A height 10mm.

Base frames are made from exterior grade satin anodised 6063-T5 magnesium

**WATER ABSORPTION**

Alumat rib infill is impervious to water, offering a superior way of dealing with incoming dirt and water. The rigid polypropylene ribs scrape footwear and collect water and dirt in the troughs, keeping them away from shoe contact. Water evaporates, and as the non-absorbent fibres are stain resistant, they are easier to clean and stay looking clean for longer. Incorporating the drain channels allows for increased water collection or drainage. Water can also easily be channelled to discharge point under the mat well.

**GUARANTEE**

ALUMAT 15D has a 20 year warranty on frame suitability for refitting with infills subject to correct installation and maintenance.

**PRICE INDICATION**

As at June 2017, ALUMAT 15 D is priced at \$659 per sq.m plus GST. (NZ freight free)